

TYPICAL RAISE/BLIND BORE MACHINE CAPABILITY MATRIX AT 12 TON/CUTTER (THEORETICAL)	COMMON MACHINE TYPE												
	24R	33/34R	43R	52R	53R	61R/65R/RBM 6	71/72R /RBM7	83/85R	97R	103R	123R	HG330	HG380
HOLE DIA.(m)													
0,7	60	60	250		350								
1,0	40	45	200		300	759	901	949	1187	1187	1774	1860	1828
1,2			150		250	651	824	899	1124	1124	1721	1808	1793
1,5			100	80	200	543	747	849	1061	1061	1668	1756	1760
1,8					165	435	669	796	995	995	1617	1704	1725
2,1						327	591	744	930	930	1565	1652	1689
2,4							513	692	865	865	1512	1600	1654
2,7							435	640	800	800	1461	1548	1619
3,1							425	634	793	793	1455	1542	1613
3,5								574	718	718	1395	1482	1578
3,8								520	650	650	1341	1428	1553
4,1								467	584	584	1287	1375	1474
4,5								405	506	506	1226	1313	1441
4,8								353	441	441	1175	1261	1406
5,1								298	373	373	1119	1207	1371
5,5								244	305	305	1067	1153	1338
5,8								195	244	244	1014	1102	1302
6,1									176	176	962	1050	1261
7,1											536	623	1032

Table 2